MONARCH 6636

66" x 36" x 20"

Monarch is a refined collection of therapeutic baths with distinctive Quartz deck surfaces, for a look that's noble and pure.



MODEL	тми	TUB
Standard (S)*	BMOLRB00T-XX	BMOLRB00N-XX
Grand Luxury (GL)*	BMLLRB00T-XX	BMLLRB00N-XX

THERMOMASSEUR (TMU) Hydro-thermo massage • Air jet system	GL \$
Jets	42
1 heated backrest	Included
MiaPlus® Control (not installed)	Included
BU-Touch Control Application BUTOUCH	\$
Geysair®	Included
AromaCloud®	N/A
Illuzio Chromatherapy BCHRO6	\$
2 nd heated backrest (WTS-1 zone) BSHB	\$

TUB Soaker	s \$	GL \$	
AromaCloud®			N/A
Illuzio Chromatherapy BCHRO6		\$	
WarmTouchShell® BWTS		\$	
DOT control		Included wit	h therapy
2 nd WarmTouchShell® BWTS2		\$	

DOT CONTROL	DOT CONTROL			included with therapy	
2 nd WarmTouchShell® BV	2 nd WarmTouchShell® BWTS2				
FEATURES					
Installation type			Drop-in & A	Alcove (3 walls)	
No. of bathers	* *	Imp. gallo	ns	42	
US gallons	50				
INTEGRATED WASTE	& OVERFLO	W BOVERINI-	ΚΧ		
White 01, Chrome 07, Br Polished Nickel 10	White 01, Chrome 07, Brushed Nickel 09, Polished Nickel 10			Installed & Included	
STANDARD COLOR (in	STANDARD COLOR (inner shell)				
White 01				Included	
QUARTZ DECK COLO	2	В	S* DMO6636-XX	GL* BDML6636-XX	
Grey Noka 22 Expo 21	Jet Black 23	Lagos Blue 24	Included	Included	

QUARTZ DECK COLOR	S* BDMO6636-XX	GL*
Quasar Light 25	\$	\$
Piatra Bianco Woodlands Grey 26 Drift 31 30	\$	\$
Statuario Maximus 29	\$	\$
FINISH (inner shell)		
UltraVelour Matte Finish (White only) BVEL		\$
INTEGRATED WASTE & OVERFLOW BOVERI	NI-XX	
Matte Black 19, Satin Brass 18		\$
WASTE & OVERFLOW 16" x 35" BOVER16-XX		
Chrome 07		\$
White 01		\$
Brushed Nickel 09, Polished Nickel 10, Oil-rubb	ed Bronze 11	\$
QUARTZ SKIRT 6618 (66" x 18 7/8") BSM6618	-XX	
Grey Expo 21, Noka 22		\$
Jet Black 23, Lagos Blue 24		\$
Quasar Light 25		\$
Piatra Grey 26, Bianco Drift 31, Woodlands 30		\$
Statuario Maximus 29		\$
TILE FLANGE (specify front or back)		
Ordered with bath (not installed) BTILEN		\$
Factory-installed. Front BTILEF, Back BTILEB, Special installation BTILEO		\$
IF REQUIRED BY CONSTRUCTION CODE		
Brass waste & overflow kit** BDRCOB		\$
Brass waste kit** BDRCB		\$
16" x 35" Cable driven brass waste & overflow	kit BOVERBR-XX	\$









MONARCH 6636

INSTALLATION





LETTER	DESCRIPTION	MEASURE
Α	Total length	66"
В	Total width	36"
С	Bathing well length (at height of jets)	46 1/8"
D	Bathing well width (at height of jets)	23 1/4"
E	Deck width (edges)	4 3/4"
F	Deck width (sides)	4 5/8"
G	Bath height	19 5/8"
Н	Height from drain to center of overflow	15 1/2"
I	Outside edge to center drain	11 3/8"
J	Slope of backrests	23°
K	Quartz deck height	3/4"

Turbine position (TMU)

Indicates heated backrest (TMU)

 Indicates WarmTouchShell® position (TUB)



Don't forget that this model is available in White only with choice of quartz deck color. Don't forget to specify the finish of the integrated waste & overflow.

* Standard: Quartz deck with seam. Grand Luxury: one piece Quartz deck.
** When ordered with integrated drain & overflow.

TOTAL PRICE

TECHNICAL SP	ECIFICATIONS			
Hot water	Should be 70% of water capacity of TUB or greater.	Approx. shipping weight	253 lbs	
supply required	Access to the pump must be at least 18" x 22". Standard connection is 20 A. 120 V, 60 hz , dedicated	Turbine power	550 W	
Turbine	line with a Ground-Fault Circuit Interrupter (GFCI). For any additional option, a second line is	Air heater	600 W	
	needed 15 A. 120 V, 60 hz, dedicated line with a GFCI.	WARRANTY		
Others	The GEYSAIR must always be accessible and connected to the hot water supply (provide access). Control cannot be installed on the Quartz deck. Optional tile flange (specify front or back).	Controls-LED-Geysair*	5 years	
		Quartz deck*	15 years	
Our products must be installed by certified professionals only and according to our Monarch Installation Manual as well as federal, provincial/state and local building codes and regulations (www.bainultra.com/documentation/documentation).		Bath & turbine*	20 years	







The specifications shown indicate the outer edge dimension and the inside bathing capacity dimension measured at air jets' height. The manufacturer accepts a 1/4" [0.64 cm] variance. There are variations on each product and specifications are subject to change as we improve upon our product as required. The dimensions needed for site preparation and structure building will differ. BainUltra® assumes no responsibility for preparatory work done prior to the product being on site.