


Submitted Model No.:



▲ Designate Proper Finish Suffix

Delta reserves the right (1) to make changes in specifications and materials, and (2) to change or discontinue models, both without notice or obligation. Dimensions are for reference only. See current full-line price book or www.deltafaucet.com for finish options and product availability. DSP-L-538T-DST Rev G



see what Delta can do

BATHROOM FAUCET

- Lahara[®] Bath Collection
- Single Handle Deck Mount

FEATURES:

- DIAMOND Seal[®] Technology
- Touch₂O._{xt}[™] Technology

STANDARD SPECIFICATIONS:

- Max. flow rate 1.20 gpm @ 60 psi, 4.54 L/min @ 414 kPa
- One or three hole mount (escutcheon optional, included)
- Diamond coated ceramic cartridge
- 3/8" O.D. straight, staggered PEX supply lines • LED indicator light signals on-off, water
- temperature and when batteries run low
- Uses 6 AA (included) or 6 C (optional) batteries Optional (EP73954) 120V AC adapter available (3 prong grounded outlet required)
- Plastic pop-up

WARRANTY

- Parts and Finish Lifetime limited warranty; or for commercial purchasers, 10 years for multi-family residential (apartments and condominiums) and 5 years for all other commercial uses, in each case from the date of purchase.
- Electronic Parts and Batteries (if applicable) 5 years from the date of purchase; or for commercial purchasers, 1 year from the date of purchase. No warranty is provided on batteries.



COMPLIES WITH:

ASME A112.18.1 / CSA B125.1
ASME A112.18.2 / CSA B125.2

- Indicates compliance to ICC/ANSI A117.1 Valve control only Verified compliant with .25% weighted average Pb content regulations.
- EPA WaterSense[®]

Delta Faucet Company

55 E. 111th Street, Indianapolis, IN 46280 350 South Edgeware Road, St. Thomas, ON N5P 4L1 © 2020 Delta Faucet Company