



**STERLING**  
10" Water Filter Housing



**H34**  
3/4" Connections  
Wrench Included  
Accepts 10" x 2-1/2" Cartridges

**STERLING**  
10" High Flow Water Filter Housing



**HJ10-1**  
1" Connections  
Wrench Included  
Accepts 10" x 4-1/2" Cartridges

**STERLING**  
10" Valve-In-Head Water Filter Housing



**VH34**  
3/4" Connections  
Wrench Included  
Accepts 10" x 2-1/2" Cartridges

# Cartridge Filter Housings

# Drinking Water Systems



...THE NEXT GENERATION

www.sterlingwatertreatment.com



# 3/4" Filter Housings



## H34

Wrench	O-Ring	Bracket
WR300	ORVH	BRK-1020

- 3/4" inlet/outlet housing
- Includes: wrench & pressure relief
- Whole house applications
- Accepts 2-1/2" x 10" cartridges
- Maximum pressure: 100 psi
- Maximum temperature: 100°F



## HW34

Wrench	O-Ring	Bracket
WR300	ORVH	BRK-1020

- 3/4" inlet/outlet housing
- Includes: wrench & pressure relief
- Whole house applications
- Accepts 2-1/2" x 10" cartridges
- Maximum pressure: 100 psi
- Maximum temperature: 100°F



## VH34

Wrench	O-Ring	Bracket
WR300	ORVH	BRK-VIH

- Valve-in-head 3/4" inlet/outlet
- Includes: wrench
- Turning the valve closes both inlet & outlet and relieves the pressure simultaneously
- Accepts 2-1/2" x 10" cartridges
- Maximum pressure: 100 psi
- Maximum temperature: 100°F



## H34SS

- 3/4" inlet/outlet housing
- Includes: bracket & screws
- Stainless steel housing
- Maximum pressure: 150 psi
- Maximum temperature: 200°F



## HL34

Wrench	O-Ring	Bracket
WR400	OR3420	BRK-1020

- 3/4" inlet/outlet housing
- Includes: wrench & pressure relief
- White sump
- Accepts 2-1/2" x 20" cartridges
- Maximum pressure: 100 psi
- Maximum temperature: 100°F



## HL34-CLEAR

Wrench	O-Ring	Bracket
WR400	OR3420-CLEAR	BRK-1020

- 3/4" inlet/outlet housing
- Includes: wrench & pressure relief
- Clear sump
- Accepts 2-1/2" x 20" cartridges
- Maximum pressure: 100 psi
- Maximum temperature: 100°F



## HOT34

Wrench	O-Ring	Bracket
WR300	OR3420	BRK-1020

- 3/4" inlet/outlet hot water housing
- Includes: wrench & pressure relief
- Maximum pressure: 100 psi
- Maximum temperature: 200°F

# 1/4" Filter Housings



## USH05

Wrench	O-Ring
WR200	ORUSH

- 1/4" inlet/outlet housing
- Includes: 3/8" adapters, bracket & wrench
- Ideal for single faucet installations
- Accepts 2-1/2" x 5" cartridges
- Maximum pressure: 100 psi
- Maximum temperature: 100°F



## USH10

Wrench	O-Ring
WR200	ORUSH

- 1/4" inlet/outlet housing
- Includes: 3/8" adapters, bracket & wrench
- Ideal for single faucet installations
- Accepts 2-1/2" x 10" cartridges
- Maximum pressure: 100 psi
- Maximum temperature: 100°F

# 1" High Flow Filter Housings



## HJ10-1

Wrench	O-Ring	Bracket
WR500	ORBB	BRK-J

- 1" inlet/outlet housing
- Includes: wrench & pressure relief
- White sump
- Suitable for high flow applications
- Accepts 4-1/2" x 10" cartridges
- Maximum pressure: 100 psi
- Maximum temperature: 100°F



## HJ10-CLEAR

Wrench	O-Ring	Bracket
WR500	ORBB-CLEAR	BRK-J

- 1" inlet/outlet housing
- Includes: wrench & pressure relief
- Clear sump
- Suitable for high flow applications
- Accepts 4-1/2" x 10" cartridges
- Maximum pressure: 100 psi
- Maximum temperature: 100°F



## HJ20-1

Wrench	O-Ring	Bracket
WR500	ORBB	BRK-J

- 1" inlet/outlet housing
- Includes: wrench & pressure relief
- White sump
- Suitable for high flow applications
- Accepts 4-1/2" x 20" cartridges
- Maximum pressure: 100 psi
- Maximum temperature: 100°F



## HJ20-CLEAR

Wrench	O-Ring	Bracket
WR500	ORBB-CLEAR	BRK-J

- 1" inlet/outlet housing
- Includes: wrench & pressure relief
- Clear sump
- Suitable for high flow applications
- Accepts 4-1/2" x 20" cartridges
- Maximum pressure: 100 psi
- Maximum temperature: 100°F

# 1.5" High Flow Filter Housings



## HJ10-15

Wrench	O-Ring	Bracket
WR500	ORBB	BRK-J

- 1.5" inlet/outlet housing
- Includes: wrench & pressure relief
- White sump
- Suitable for high flow applications
- Accepts 4-1/2" x 10" cartridges
- Maximum pressure: 100 psi
- Maximum temperature: 100°F



## HJ20-15

Wrench	O-Ring	Bracket
WR500	ORBB	BRK-J

- 1.5" inlet/outlet housing
- Includes: wrench & pressure relief
- White sump
- Suitable for high flow applications
- Accepts 4-1/2" x 20" cartridges
- Maximum pressure: 100 psi
- Maximum temperature: 100°F

# Drinking Water Systems

## Reverse Osmosis Systems



### DWSB-TFC-50

5 Stage Reverse Osmosis System  
5 Micron Sediment, GAC, Carbon Block,



### QCRO-50

5 Stage Reverse Osmosis System  
Sanitary Quick Change Cartridges. Fast & Simple cartridge replacement.



### CRS-3

Cyst, Virus & Chemical  
Reduction System



### Q1-CB1

Sanitary Quick Change  
Carbon Block



### Q1-SR1

Sanitary Quick Change  
Scale Inhibitor & Carbon



### S500SS

Scale Inhibitor  
System

## Pump Model R.O. Systems



### RO-LSV

Leak Detector Stop Valve



### DWSB-50-PermPump

4 Stage Reverse Osmosis System



### QCRO-50-PUMP

5 Stage Reverse Osmosis System  
Quiet booster pump increases water pressure to improve water quality and quantity.

## Specialty Systems



### ARS-1

Arsenic Reduction System  
With metered auto shut-off



### NRS-1

Nitrate Reduction System  
With metered auto shut-off

